

## **FEATURES - FLEXO WATER WASH TOWER**

- 9 channels controller of each working step simultaneously: Pre-exposure time, Main Exp. Time, UVC Exposure time, Post-exposure time, Processing temperature, Processing time, Dryer temperature, Dryer time (for each drawer)
- Exposure section equipped with suction surface that grants, together with the high quantity of lamps, a uniform covering
- Plate processing in stainless steel tank, via the orbital action of a plate-holder table, (overturnable in A1 model) and a set of brushes, adjustable in their height
- The anti-tack (model A3 and A2) and anti-tack post-exposure (model A1) sections are totally in stainless steel and they have a suction separated from the wash-out tank and dryer one
- Lamp hour counter
- Sand filtration unit

	<b>A3FLW</b>	<b>A2FLW</b>	<b>A1FLW</b>
<b>Max plate size (mm)</b>	370x520	530x760	710x890
<b>Max plate size (inches)</b>	14"x20"	20"x29"	27"x35"
<b>UVA exposure lamps</b>	9x40W 10R L. 590	12x60W 10R L. 900	15x60W 10R L. 1200
<b>UVC lamps</b>	10x15W L. 437	12x30W L. 900	13x36W L. 1200
<b>UVA post-exposure lamps</b>	-	-	14x60W 10R L. 1200
<b>Stainless steel tank (l)</b>	27	50	110
<b>Wattage (kW)</b>	3,5	10	10
<b>Heater (W)</b>	2x600	4x600	6x600
<b>Electrical supply</b>	230V (3PH+GND) 60Hz 400V (3PH+N+GND) 50Hz		
<b>Overall size (LxWxH) (cm)</b>	75x105x120	108x110x120	145x115x135
<b>Weight (kgs)</b>	210	310	520